

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : PRO 45P - Fast PU Wood Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Main use category : Consumer use, Professional use
Use of the substance/mixture : adhesives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Soudal N.V. N.V.
Everdongenlaan 18-20
2300 Turnhout
Belgium
T +32 14 42 42 31 - F +32 14 42 65 14
sds@soudal.com - www.Soudal.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Respiratory sensitisation, Category 1 H334
Skin sensitisation, Category 1 H317
Carcinogenicity, Category 2 H351
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation H335
Specific target organ toxicity – Repeated exposure, Category 2 H373
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

Signal word (CLP)

: Danger

Contains

: polymethylene polyphenyl isocyanate

Hazard statements (CLP)

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Extra phrases

: Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component

polymethylene polyphenyl isocyanate (9016-87-9)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
polymethylene polyphenyl isocyanate	CAS-No.: 9016-87-9	≥ 50 – < 75	Carc. 2, H351 Resp. Sens. 1, H334 Skin Sens. 1, H317 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
reaction mass of ethylbenzene and xylene	EC-No.: 905-588-0 REACH-no: 01-2119488216-32	≥ 5 – < 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Comments : polymethylene polyphenyl isocyanate, contains > 0.1% MDI isomers
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Rinse mouth out with water. Do NOT induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Cough. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. EXPOSURE TO HIGH CONCENTRATIONS: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Dry/sore throat.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Irritation of the gastric/intestinal mucosa. AFTER INGESTION OF HIGH QUANTITIES: Central nervous system depression. Enlargement/affection of the liver.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

- Reactivity in case of fire : Reacts with water: release of toxic/harmful substances. Hydrogen cyanide. Reacts slowly with water, generate gases (CO₂) and overpressure : rupture containers.
- Hazardous decomposition products in case of fire : On burning: release of carbon monoxide - carbon dioxide. Nitrous fumes.

5.3. Advice for firefighters

- Firefighting instructions : Cool closed containers exposed to fire with water spray. Do not allow water to enter the vessels, a violent reaction may occur. Dilute toxic gases with water spray.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No open flames. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill.
- Methods for cleaning up : Leave the product to solidify.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapours. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Keep away from naked flames/heat. Keep only in original container.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Incompatible products : Moisture. Reacts with water. Strong acids. Strong bases.
- Incompatible materials : Heat sources.
- Packaging materials : Synthetic material.

7.3. Specific end use(s)

No additional information available

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

reaction mass of ethylbenzene and xylene	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	442 mg/m ³
Acute - local effects, inhalation	442 mg/m ³
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m ³
Long-term - local effects, inhalation	221 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, inhalation	260 mg/m ³
Long-term - systemic effects, oral	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65,3 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,327 mg/l
PNEC aqua (marine water)	0,327 mg/l
PNEC aqua (intermittent, freshwater)	0,327 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,31 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	6,58 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Measure concentrations regularly, and at the time of any change occurring in conditions likely to have consequences on workers exposure.

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or face shield. EN 166

8.2.2.2. Skin protection

Skin and body protection:

Protective clothing (EN 14605 or EN 13034)

Hand protection:

Protective gloves against chemicals (EN 374)

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Appearance	: Liquid.
Odour	: solvent-like.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: ≈ 80,5 °C (ISO 2719A)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 1100 kg/m ³ (20°C)
Relative density	: 1,1 (20°C)
Relative vapour density at 20 °C	: > 2
Particle characteristics	: Not applicable

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 7,5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Moisture sensitive.

10.3. Possibility of hazardous reactions

Reacts with water, generates gases or heat and overpressure : rupture containers. Reacts with (some) acids/bases. Reacts with (some) acids. alcohol. Amines.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

water. alcohols. Amines. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On burning: release of (highly) toxic gases/vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

PRO 45P - Fast PU Wood Adhesive	
ATE CLP (dust,mist)	2,422 mg/l/4h
reaction mass of ethylbenzene and xylene	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
polymethylene polyphenyl isocyanate (9016-87-9)	
LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
LC50 Inhalation - Rat	10 – 20 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.
Reproductive toxicity : Not classified

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

STOT-single exposure : May cause respiratory irritation.

reaction mass of ethylbenzene and xylene

STOT-single exposure : May cause respiratory irritation.

polymethylene polyphenyl isocyanate (9016-87-9)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

reaction mass of ethylbenzene and xylene

LOAEL (oral, rat, 90 days) : 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

polymethylene polyphenyl isocyanate (9016-87-9)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure (if inhaled).

Aspiration hazard : Not classified

reaction mass of ethylbenzene and xylene

Viscosity, kinematic : $\approx 0,76 \text{ mm}^2/\text{s}$ Temp.: '20°C' Parameter: 'kinematic viscosity (in mm^2/s)'

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

reaction mass of ethylbenzene and xylene

EC50 - Crustacea [1] : > 3,4 mg/l Test organisms (species): Ceriodaphnia dubia

LOEC (chronic) : 3,16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

NOEC chronic fish : > 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

polymethylene polyphenyl isocyanate (9016-87-9)

LC50 - Other aquatic organisms [1] : > 1000 mg/l (96 h, Literature study)

12.2. Persistence and degradability

polymethylene polyphenyl isocyanate (9016-87-9)

Persistence and degradability : not readily degradable in water.

12.3. Bioaccumulative potential

polymethylene polyphenyl isocyanate (9016-87-9)

BCF - Fish [1] : 1 (Pisces, Literature study)

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

polymethylene polyphenyl isocyanate (9016-87-9)

Partition coefficient n-octanol/water (Log Pow)	10,46 (Calculated, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

polymethylene polyphenyl isocyanate (9016-87-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9,078 – 10,597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Adsorbs into the soil.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Collect all waste in suitable and labelled containers and dispose according to local legislation.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(b)	PRO 45P - Fast PU Wood Adhesive ; reaction mass of ethylbenzene and xylene ; polymethylene polyphenyl isocyanate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(a)	reaction mass of ethylbenzene and xylene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
56.	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI)
56(a)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl diisocyanate
56(b)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,4'-Methylenediphenyl diisocyanate
56(c)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,2'-Methylenediphenyl diisocyanate
74.	polymethylene polyphenyl isocyanate	Diisocyanates, $O = C = N - R - N = C = O$, with R an aliphatic or aromatic hydrocarbon unit of unspecified length

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

VOC Directive (2004/42)

VOC content : < 7,5 %

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878		
2		Modified	
3.2		Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

PRO 45P - Fast PU Wood Adhesive

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

Safety Data Sheet (SDS), EU-20221

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.