


First for service, second to none

U-Bolt Range Technical Information Sheet

BZP U-Bolts – Standard Leg




The dimension given for U-bolts is the nominal bore (N.B.) of the pipe. The actual distance between the legs is greater than this to allow for the wall thickness of the pipe. All our U-bolts are supplied with two hex nuts to suit.

ORDER CODE	NB mm	NB INCHES	MATERIAL/ FINISH	A mm	B mm	C mm	D mm	QTY
R621-110	20mm	³ /4"	BZP	27	53	30	M6	100
R621-112	25mm	1"	BZP	34	60	30	M6	100
R621-116	32mm	1 ¹ /4"	BZP	45	70	40	M10	100
R621-120	40mm	1 ¹ / ₂ "	BZP	51	75	40	M10	100
R621-125	50mm	2"	BZP	60	85	40	M10	100
R621-132	65mm	2 ¹ / ₂ "	BZP	76	100	40	M10	100
R621-140	80mm	3"	BZP	90	115	40	M12	100
R621-150	00mm	4"	BZP	114	140	40	M12	100
R621-155	125mm	5"	BZP	140	165	40	M12	100
R621-160	150mm	6"	BZP	170	200	50	M12	100

Dimension 'A' is outside diameter. Distance between legs will be greater than this. Supplied complete with two nuts.

BZP U-Bolts – Extended Leg



The dimension given for U–bolts is the nominal bore (N.B.) of the pipe. The actual distance between the legs is greater than this to allow for the wall thickness of the pipe. Extended leg U–bolts have approximately 50mm extra thread length on the legs than standard U–bolts. All our U–bolts are supplied with two hex nuts to suit.

ORDER CODE	NB mm	NB INCHES	MATERIAL/ FINISH	A mm	B mm	C mm	D mm	QTY
R621-212	25mm	1"	BZP	34	111	75	M6	100
R621-216	32mm	1 ¹ /4"	BZP	45	122	85	M10	100
R621-220	40mm	1 ¹ /2"	BZP	48	127	85	M10	100
R621-225	50mm	2"	BZP	60	140	85	M10	100
R621-232	65mm	2 ¹ / ₂ "	BZP	76	152	85	M10	100
R621-240	80mm	3"	BZP	90	168	90	M10	100
R621-250	100mm	4"	BZP	114	193	90	M12	100
R621-270	200mm	8"	BZP	215	295	90	M12	100

Dimension 'A' is outside diameter. Distance between legs will be greater than this. Supplied complete with two nuts. All sizes given are approximate.

Stainless Steel U-Bolts – Standard Leg

The dimension given for U–bolts is the nominal bore (N.B.) of the pipe. The actual distance between the legs is greater than this to allow for the wall thickness of the pipe. All our U–bolts are supplied with two hex nuts to suit. See BZP U-Bolts for further details on sizing.

ORDER CODE	NB mm	NB INCHES	MATERIAL/ FINISH	QTY
R624-007	15mm	1/2"	Stainless Steel	100
R624-110	20mm	3/4"	Stainless Steel	100
R624-112	25mm	1"	Stainless Steel	100
R624-116	32mm	1 ¹ / ₄ "	Stainless Steel	100
R624-120	40mm	1 ¹ /2"	Stainless Steel	100
R624-125	50mm	2"	Stainless Steel	100





First for service, second to none

Pipe Sizing Grid Technical Information Sheet

S	COPPER PIPE SIZES			
SIZE (INCH) NB	SIZE (METRIC) NB	OUTSIDE DIAMETER OF PIPE (mm)	OUTSIDE DIAMETER OF PIPE (mm)	
1/2	15	21.3	15	
3/4	20	26.9	22	
1	25	33.7	28	
1 1/4	32	42.4	35	
1 1/2	40	48.3	42	
2	50	60.3	54	
2 1/2	65	76.1	66/67	
3	80	88.9	76	
4	100	114.3	108	
5	125	139.7	133	
6	150	168.3	159	
7	175	193.7	-	
8	200	219.1	219	
9	225	244.5	-	
10	250	273	270	
12	300	323.9	323	
14	350	355.6	-	
16	400	406	-	
18	450	457	-	
20	500	508	-	
22	550	559	-	
24	600	610	-	