



Tectane Penetrating Oil MoS2 Penetrating oil with molybdenum



Product Description

Penetrating Oil is a well-established lubricant and rust remover. Penetrating Oil solves, effortlessly and fast, a number of problems with servicing, repairs, maintenance and production. With cleaning and repairs, the problem always arises that old, corroded connections and screwed joints have to be unfastened.

Benefits

- Unfastening connections, such as screwed joints, nuts and bolts, which have become stuck through rust
- Offering lasting protection from corrosion
- · Greasing sliding surfaces
- · Removing squeaking and creaking noises
- Cleaning brake linkages, bowden cables, chains of all sorts and keeping them in good condition

Applications

The well-balanced selection of raw materials results in an immediate effect on badly corroded connections. Its strong capillary action and excellent flow properties enable Penetrating Oil to find its way into the smallest of spaces. The anti-corrosion components in the product prevent new rust from being formed on parts treated. The easy way of handling Penetrating Oil in aerosols enables the consumer to handle it safely and to use it in an economic way by applying it right on the rust spot. Tectane Penetrating Oil can be used for car maintenance, industry, household, marine etc.

Directions Of Use

Shake the aerosol vigorously before use. Afterwards, moisten the spot that needs treating covering the whole area with the product. After waiting a few minutes, the connection treated can be unfastened.

Additional information

Base	Hydrocarbons
Density	0.704
Extrusion rate gs	1.8
Frost resistance during transportation	Up to - 15°C
Pressure at 20c bar	4.2
Pressure at 50c bar	7.9
Solid contents	<1

These values are typical properties and may vary +/-3%

Limitations

Surface Preparations and Finishing

Cleaning

Issue11/29.04.16/0013.11.DBA

Colour(s)

•

Packaging

Aerosol

For product specifications, please refer to the Product Detail Page

Shelf Life

Storage between + 5° C and +2 5° C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.





Technical Data Sheet

Tectane Penetrating Oil MoS2 Penetrating oil with molybdenum

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

XSXSXSX

Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. The user may either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the product sprior to the use the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for

damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

