SAFETY DATA SHEET

PREMIUM WOOD ADHESIVE

Page 1 Issued: 11/04/2003 Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PREMIUM WOOD ADHESIVE

Product code: WOOD - ALL SIZES

Use / description of product: No significant hazard.

Company name: PREMIUM ADHESIVES

Care Line Tel: 0800 6888 982

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: BUTYL DIGLYCOL ACETATE 1-10%

[Xi] R36/38

 ALUMINIUM CHLORIDE, ANHYDROUS 1-10% CAS: 7446-70-0

EINECS: 231-208-1

[C] R34

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

5. FIRE-FIGHTING MEASURES

Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool
	containers.
Exposure hazards:	In combustion emits toxic fumes.
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin
	and eyes.

SAFETY DATA SHEET

PREMIUM WOOD ADHESIVE

6. ACCIDENTAL RELEASE	E MEASURES	
Personal precautions:	Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up	
	to prevent the escape of liquid.	
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.	
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by	
	an appropriate method.	
7. HANDLING AND STORAGE		
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed. Store in original containers	
	between +5 and +25°C. Storage outside these paramaters will dramatically reduce shelf life and	
	invalidates all product warrenties.	
Suitable packaging:	Must only be kept in original packaging.	
8. EXPOSURE CONTROLS	/ PERSONAL PROTECTION	
Ingredients:	ALUMINIUM CHLORIDE, ANHYDROUS	
	TWA (8 hr exposure limit): 2mg/m3 (OES)	
Respiratory protection:	Respiratory protection not required.	
Hand protection:	Protective gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Protective clothing.	
9. PHYSICAL AND CHEMI	CAL PROPERTIES	
State:	Liquid	
Colour:	White	
Odour:	Pleasant	
Viscosity:	Viscous	
Boiling point/range°C:	100	
Relative density:	1.03-1.07	
pH:	3.5-5	
10. STABILITY AND REAC		
Stability:	Stable under normal conditions.	
Conditions to avoid:	Heat. Protect from frost	
Materials to avoid:	Strong oxidising agents. Strong acids.	
Haz. decomp. products:	In combustion emits toxic fumes.	
11. TOXICOLOGICAL INFO	DRMATION	
Ingredients:	ALUMINIUM CHLORIDE, ANHYDROUS	
	ORL MUS LD50 390 mg/kg	
	ORL RAT LD50 315 mg/kg	
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.	

[cont...]

SAFETY DATA SHEET

PREMIUM WOOD ADHESIVE

12. ECOLOGICAL INFORMATION		
Mobility:	Readily absorbed into soil.	
Persistence and degradability:	Biodegradable.	
Bioaccumulative potential:	No bioaccumulation potential.	
Other adverse effects:	Negligible ecotoxicity.	
13. DISPOSAL CONSIDERATIONS		
Disposal of packaging:	Dispose of as normal industrial waste.	
NB:	The user's attention is drawn to the possible existence of regional or national regulations	
	regarding disposal.	
14. TRANSPORT INFORMATION		
ADR / RID		
UN no:	-	
Shipping name:	"NOT SUBJECT TO ADR"	

IMDG / IMO		
UN no:	-	
IATA / ICAO		
UN no:	-	
15. REGULATORY INFORMATION		
Hazard symbols:	No significant hazard.	
Note:	The regulatory information given above only indicates the principal regulations specifically	
	applicable to the product described in the safety data sheet. The user's attention is drawn to	
	the possible existence of additional provisions which complete these regulations. Refer to all	

16. ADDITIONAL INFORMATION

Risk phrases used in s.2:	R36/38: Irritating to eyes and skin.
	R34: Causes burns.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and shall
	be used only as a guide. This company shall not be held liable for any damage resulting from
	handling or from contact with the above product.

applicable national, international and local regulations or provisions.