



SAFETY DATA SHEET

SCHTUK EXTREME™

Page 1

Issued: 31/05/13

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING	
Product name:	SCHTUK EXTREME™ MS Polymer Multi Adhesive & Sealant
Product code:	M072-105
Company name:	STRONGFAST - UK
Emergency tel:	0844 887 1401 (office hours only)
Website:	www.strongfast.uk.com
2. HAZARDS IDENTIFICATION	
Main hazards:	No significant hazard.
Other hazards:	This product is not classified as hazardous according to current CHIP legislation
3. COMPOSITION / INFORMATION ON INGREDIENTS	
Hazardous ingredients:	TRIMETHOXYVINYL-SILANE 1-10% CAS: 2768-02-7 [-] R10; [Xn] R20 • BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE <1% EINECS: 255-437-1 CAS: 041556-26-7 [N] R50/53; [Sens.] R43
4. FIRST AID MEASURES (SYMPTOMS)	
Skin contact:	There may be mild irritation at the site of contact.
Eye contact:	There may be irritation and redness.
Ingestion:	There may be irritation of the throat.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.
4. FIRST AID MEASURES (ACTION)	
Skin contact:	Wash immediately with plenty of soap and water.
Eye contact:	Bathe the eye with running water for 15 minutes.
Ingestion:	Wash out mouth with water.
Inhalation:	Consult a doctor.

5. FIRE-FIGHTING MEASURES	
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used.
Exposure hazards:	In combustion emits toxic fumes.
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
6. ACCIDENTAL RELEASE MEASURES	
Personal precautions:	Refer to section 8 of SDS for personal protection details.
Environmental precautions:	Do not discharge into drains or rivers.
Clean-up procedures:	Wash the spillage site with large amounts of water.
7. HANDLING AND STORAGE	
Handling requirements:	Avoid direct contact with the substance.
Storage conditions:	Store in cool, well ventilated area.
Suitable packaging:	Must only be kept in original packaging.
8. EXPOSURE CONTROLS / PERSONAL PROTECTION	
Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Respiratory protection not required.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
9. PHYSICAL AND CHEMICAL PROPERTIES	
State:	Paste
Colour:	Various
Odour:	Barely perceptible odour



SAFETY DATA SHEET

SCHTUK EXTREME™

Evaporation rate:	Negligible
Solubility in water:	Insoluble
Also soluble in:	Most organic solvents.
Viscosity:	Highly viscous
Flammability limits %: lower:	N/A
upper:	N/A
Flash point°C:	N/A
Autoflammability°C:	N/A
Relative density:	1.53
10. STABILITY AND REACTIVITY	
Stability:	Stable under normal conditions.
Conditions to avoid:	Heat.
Materials to avoid:	Strong oxidising agents. Strong acids.
Haz. decomp. products:	In combustion emits toxic fumes.
11. TOXICOLOGICAL INFORMATION	
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.
12. ECOLOGICAL INFORMATION	
Persistence and degradability:	Not biodegradable.
Bioaccumulative potential:	No bioaccumulation potential.
Other adverse effects:	Negligible ecotoxicity.

SAFETY DATA SHEET

SCHTUK EXTREME™

13. DISPOSAL CONSIDERATIONS	
Disposal operations:	Dispose of according to local or national legislation
Disposal of packaging:	Dispose of as normal industrial waste.
NB:	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.
14. TRANSPORT INFORMATION	
ADR / RID	UN no: Not Classified.
IMDG / IMO	UN no: Not Classified.
IATA / ICAO	UN no: Not Classified.
15. REGULATORY INFORMATION	
Hazard symbols:	No significant hazard.
Safety phrases:	S2: Keep out of the reach of children. S46: If swallowed, seek medical advice immediately and show this container or label.
Precautionary phrases:	Contains 3-(2-aminoethylamino)propyl trimethoxysilane, bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction.
Water hazard class:	1
Note:	The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.
16. OTHER INFORMATION	
Risk phrases used in s.3:	R10: Flammable. R20: Harmful by inhalation. R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R43: May cause sensitisation by skin contact.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.